

Trailer Specifications

Trailer Fitted With Resin Coated Plywood Platform
 Aluminium Treadplate Floor Covering
 Removable Headboard, Dropsides & Tailboard
 Dropside Fittings
 Removable Headboard
 Removable Ladder Rack (Headboard Required)
 1.8m / 6' Long Perforated Galvanized Steel Skids (Pair) (Including Prop Stands)
 1.8m / 6' Long Aluminium Skids (Pair) (Including Prop Stands)
 2.4m / 8' Long Aluminium Galvanized Steel Skids (Pair) (Including Prop Stands)
 2.4m / 8' Long Perforated Galvanized Steel Skids (Pair) (Including Prop Stands)
 Weldmesh Panelled Side Extensions
 Recessed Lashing Ring (Pair)
 6' Full Width Loading Ramp (Including Prop Stands)
 Lashing Straps (3m & 8m)
 Mud Flaps

Flatbed Trailers

LT Series	Maximum Gross Weight	Tyres	Unladen Weight	Option	Option	Std	Option	Option	Option	Option	Option	-	-	Option ^{††}	Option	Option	Option	Option
LT85	2000kg	145R10C	450kg	Option	Option	Std	Option	Option	Option	Option	Option	-	-	Option ^{††}	Option	Option	Option	Option
LT105	2000kg	145R10C	510kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option
LT125	2000kg	145R10C	565kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option
LT106	2000kg	145R10C	555kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option
LT126	2000kg	145R10C	615kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option
LT146	2000kg	145R10C	660kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option

LM 5-Series

LM85	2700kg	195/60R12C	495kg	Option	Option	Std	Option	Option	Option	Option	Option	-	-	Option ^{††}	Option	Option	Option	Option
LM105	2700kg	195/60R12C	575kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option
LM125	2700kg	195/60R12C	620kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option

3500kg Gross version available (add 30kg)

LM 6-Series

LM106	3500kg	195/60R12C	620kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option
LM126	3500kg	195/60R12C	675kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option
LM146	3500kg	195/60R12C	735kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option
LM166	3500kg	195/60R12C	795kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option
LM186	3500kg	195/60R12C	855kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option

Tri-axle version on 12', 14', 16' & 18' models (add 110kg)

LM 7-Series

LM127	3500kg	195/60R12C	705kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option
LM147	3500kg	195/60R12C	775kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option
LM167	3500kg	195/60R12C	845kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option
LM187	3500kg	195/60R12C	915kg	Option	Option	Std	Option	Option	Option	Option	Option	Option	Option	Option ^{††}	Option	Option	Option	Option

Tri-axle version on 14', 16' & 18' models (add 110kg)

Beavertail Trailers

LT146/B	2000kg	145R10C	685kg	Option	Option [†]	Option ^{**}	Option	Option	Option	Option	Option	-	-	-	Option	Option	Option	Option
LM146/B	3500kg	195/60R12C	725kg	Option	Option [†]	Option ^{**}	Option	Option	Option	Option	Option	-	-	-	Option	Option	Option	Option
LM147/B	3500kg	195/60R12C	780kg	Option	Option [†]	Option ^{**}	Option	Option	Option	Option	Option	-	-	-	Option	Option	Option	Option
LM166/B	3500kg	195/60R12C	785kg	Option	Option [†]	Option ^{**}	Option	Option	Option	Option	Option	-	-	-	Option	Option	Option	Option
LM167/B	3500kg	195/60R12C	875kg	Option	Option [†]	Option ^{**}	Option	Option	Option	Option	Option	-	-	-	Option	Option	Option	Option

Tiltbed Trailers

CT166	3500kg	195/60R12C	885kg	Option	Option [*]	Std	Option	Option	-	-	-	-	-	Option	Option	-	Option	Option
CT167	3500kg	195/60R12C	985kg	Option	Option [*]	Std	Option	Option	-	-	-	-	-	Option	Option	-	Option	Option

Other optional extras

Braked Manual winch 2000kg
 Braked Manual winch 3000kg
 Electric winch
 (Manual winch not available on CT models)

Optional accessories have been priced as factory fit items, ordered with your trailer. If ordered at a later date, your distributor may need to fit the items, which will result in fitting charges being incurred.

* Excludes tailboard: a standard ramp (1') is included within the trailer price.

† Must be specified at time of order, requires dropside fittings.

** Dropside Fittings - Must be specified at time of order, factory fit only.

†† Headboard, dropsides and tailboard required to fit meshsides.

Trailer Specifications

Trailer With Tailboard

Trailer With Loading Ramp

Aluminium Treadplate Floor Covering

Removable Ladder Rack

Weldmesh Panelled Side Extensions (Tailboard Models)

Weldmesh Panelled Side Extensions (Ramp Models)

Prop Stands (Pair)

2.4m / 8' Long Perforated Galvanized Steel Skids (Pair) (Including Prop Stands)

2.4m / 8' Long Aluminium Skids (Pair) (Including Prop Stands)

Recessed Lashing Ring (Pair)

Lashing Straps (3m & 8m)

Canopy

General Duty Trailers

	Maximum Gross Weight	Tyres	Unladen Weight	Unladen Weight										
GD 4-Series														
GD64 Single Axle	1400kg	165R13C	325kg	355kg	Option	Option	Option	Option	Std	-	-	Option	Option	Option
GD84 Single Axle	1400kg	165R13C	355kg	385kg	Option	Option	Option	Option	Std	-	-	Option	Option	Option
GD84 Single Axle	1500kg	175/75R16C	395kg	415kg	Option	Option	Option	Option	Std	-	-	Option	Option	Option
GD84 Single Axle	1500kg	6.50R16C	400kg	420kg	Option	Option	Option	Option	Std	-	-	Option	Option	Option
GD84	2700kg	165R13C	450kg	480kg	Option	Option	Option	Option	Option	-	-	Option	Option	Option
GD 5-Series														
GD85 Single Axle	1400kg	165R13C	395kg	430kg	Option	Option	Option	Option	Std	-	-	Option	Option	Option
GD85	2700kg	165R13C	485kg	525kg	Option	Option	Option	Option	Option	-	-	Option	Option	Option
GD105	2700kg	165R13C	550kg	585kg	Option	Option	Option	Option	Option	-	-	Option	Option	Option
GD125	2700kg	165R13C	585kg	620kg	Option	Option	Option	Option	Option	-	-	Option	Option	Option
GD 6-Series														
GD106	2700kg	165R13C	600kg	625kg	Option	Option	Option	Option	Option	-	-	Option	Option	Option
GD126	2700kg	165R13C	625kg	660kg	Option	Option	Option	Option	Option	-	-	Option	Option	Option
Tipping Trailers														
TT85 (Manual Pump)	2700kg	165R13C	675kg	-	Option	Std	Option	-	-	-	-	Option	Option	-
TT85E Power-Tip	2700kg	165R13C	710kg	-	Option	Std	Option	-	-	-	-	Option	Option	-
TT105 Power-Tip	3500kg	195/60R12C	965kg	-	Std*	Std	Option	-	Option	Option	Option	Option	Option	-
TT126 Power-Tip	3500kg	195/60R12C	1135kg	-	Std*	Std	Option	-	Option	Option	Option	Option	Option	-

Other optional extras (LT, LM & GD models)

- Braked Manual winch 2000kg
- Braked Manual winch 3000kg
- Electric winch
- Canopy (GD Models)

Optional accessories have been priced as factory fit items, ordered with your trailer. If ordered at a later date, your distributor may need to fit the items, which will result in fitting charges being incurred.

*Plain Aluminium Covering

All trailer weights are unladen and include standard options, these weights are for guidance only.



The Ifor Williams commitment to trailer security

Each trailer is fitted with an ID plate which has a unique serial number etched on it. Additionally, the drawbar has a different unique number cut through it†, which is virtually impossible to alter without noticeably affecting the appearance of the numbers and galvanized finish.

†Excludes GD64 & GD84 Single Axle Models.

**IFOR WILLIAMS
TRAILERS HAVE A SPARE
WHEEL FITTED AS
STANDARD**

Plant Trailers

165R13C 8PR Tyres

155/70R12C Tyres

195/60R12C Tyres

175/75R16C Tyres

6.50R16C 10PR Tyres

Aluminium Treadplate Platform Covering

Weldmesh Panelled Side Extensions

Ladder Rack

Integral Ramp/Skid Support System

Integrated Lashing Points

Aluminium Treadplate Walk-on Mudguards

Bucket Rest

Recessed Lashing Ring (Pair)

Lashing Straps 8m (Each)

Lashing Straps 3m (Each)

Knife Edge for Ramp

Filled in Sides

	Maximum Gross Weight	Unladen Weight	Unladen Weight	Unladen Weight	Unladen Weight	Unladen Weight													
GX Series																			
GX84 Skids	2700kg	540kg	-	-	-	-	Option	-	Option	Std	Std	-	Std	Option	Option	Option	Option	Option	Std
GX84 Ramp	2700kg	540kg	-	-	-	-	Option	Option	Option	Std	Std	-	Std	Option	Option	Option	Option	Option	Std
GX105 Skids	2700kg	660kg	-	-	-	-	Option	-	Option	Std	Std	-	Std	Option	Option	Option	Option	Option	Std
GX105 Ramp	2700kg	675kg	-	-	-	-	Option	Option	Option	Std	Std	-	Std	Option	Option	Option	Option	Option	Std
GX105 H/D Skids	3500kg	-	670kg	-	-	-	Option	-	Option	Std	Std	-	Std	Option	Option	Option	Option	Option	Std
GX105 H/D Ramp	3500kg	-	690kg	-	-	-	Option	Option	Option	Std	Std	-	Std	Option	Option	Option	Option	Option	Std
GX125 H/D Skids	3500kg	-	740kg	-	-	-	Option	-	Option	Std	Std	-	Std	Option	Option	Option	Option	Option	Std
GX125 H/D Ramp	3500kg	-	760kg	-	-	-	Option	Option	Option	Std	Std	-	Std	Option	Option	Option	Option	Option	Std
GX106 Skids	3500kg	-	700kg	-	-	-	Option	-	Option	Std	Std	-	Std	Option	Option	Option	Option	Option	Std
GX106 Ramp	3500kg	-	715kg	-	-	-	Option	Option	Option	Std	Std	-	Std	Option	Option	Option	Option	Option	Std
GX126 Skids	3500kg	-	765kg	-	-	-	Option	-	Option	Std	Std	-	Std	Option	Option	Option	Option	Option	Std
GX126 Ramp	3500kg	-	795kg	-	-	-	Option	Option	Option	Std	Std	-	Std	Option	Option	Option	Option	Option	Std
GX126 Tri-Axle Skids	3500kg	-	875kg	-	-	-	Option	-	Option	Std	Std	-	Std	Option	Option	Option	Option	Option	Std
GX126 Tri-Axle Ramp	3500kg	-	890kg	-	-	-	Option	Option	Option	Std	Std	-	Std	Option	Option	Option	Option	Option	Std
GH Series																			
GH94†	2700kg	-	-	490kg	-	-	Option	-	-	Std	Std*	Std	Std	-	Option	Option	-	-	Std
GP-Low Sides																			
GP106 Skids	3500kg	-	705kg	705kg	765kg	780kg	Option	-	-	Std	Std	Std	Std	Option	Option	Option	Option	Option	Option
GP106 Ramp	3500kg	-	720kg	720kg	780kg	795kg	Option	-	-	Std	Std	Std	Std	Option	Option	Option	Option	Option	Option
GP126 Skids	3500kg	-	780kg	780kg	840kg	855kg	Option	-	-	Std	Std	Std	Std	Option	Option	Option	Option	Option	Option
GP126 Ramp	3500kg	-	795kg	795kg	855kg	870kg	Option	-	-	Std	Std	Std	Std	Option	Option	Option	Option	Option	Option
GP126 Tri-Axle Skids	3500kg	-	890kg	890kg	980kg	-	Option	-	-	Std	Std	Std	Std	Option	Option	Option	Option	Option	Option
GP126 Tri-Axle Ramp	3500kg	-	905kg	905kg	995kg	-	Option	-	-	Std	Std	Std	Std	Option	Option	Option	Option	Option	Option
GP146 Tri-Axle Skids	3500kg	-	915kg	915kg	1005kg	-	Option	-	-	Std	Std	Std	Std	Option	Option	Option	Option	Option	Option
GP146 Tri-Axle Ramp	3500kg	-	930kg	930kg	1020kg	-	Option	-	-	Std	Std	Std	Std	Option	Option	Option	Option	Option	Option
GP-High Sides																			
GP106H Skids	3500kg	-	785kg	785kg	845kg	860kg	Option	-	Option	Std	-	Std	Option	Option	Option	Option	Option	Option	Std
GP106H Ramp	3500kg	-	800kg	800kg	860kg	875kg	Option	Option	Option	Std	-	Std	Option	Option	Option	Option	Option	Option	Std
GP126H Skids	3500kg	-	870kg	870kg	930kg	945kg	Option	-	Option	Std	-	Std	Option	Option	Option	Option	Option	Option	Std
GP126H Ramp	3500kg	-	885kg	885kg	945kg	960kg	Option	Option	Option	Std	-	Std	Option	Option	Option	Option	Option	Option	Std
GP126H Tri-Axle Skids	3500kg	-	980kg	980kg	1070kg	-	Option	-	Option	Std	-	Std	Option	Option	Option	Option	Option	Option	Std
GP126H Tri-Axle Ramp	3500kg	-	995kg	995kg	1085kg	-	Option	Option	Option	Std	-	Std	Option	Option	Option	Option	Option	Option	Std
GP146H Tri-Axle Skids	3500kg	-	1095kg	1095kg	1105kg	-	Option	-	Option	Std	-	Std	Option	Option	Option	Option	Option	Option	Std
GP146H Tri-Axle Ramp	3500kg	-	1030kg	1030kg	1120kg	-	Option	-	Option	Std	-	Std	Option	Option	Option	Option	Option	Option	Std

H/D - Heavy Duty, H - High Sided
 Standard ramp and skids length, 4'. Trailers also available with 6' ramp or skids.
 All trailer weights are unladen and include standard options, these weights are for guidance only.
 * GH94 has 5 pairs of integral lashing points per trailer (non recessed).
 † GH94 does not include a spare wheel fitted as standard. Available with 3'11" ramp with mesh infill or 4'10" ramp without mesh infill.