

Livestock Trailer Specifications

Trailer fitted with EasyLoad™ Ramp and Aluminium Sheep Deck System

Trailer fitted with Standard Ramp without Sheep Deck

Trailer fitted with Combination Ramp Doors without Sheep Deck*

Cross Division

Small Cross Division (for use with Sheep Deck System only)

Wind Deflector

Ramp Gate Extensions (Pair)

Centre Partition Kit (7' Headroom Models only)

Breast Bar Only (for use with Centre Partition Kit only)

Sump Tank

Prop Stands (Pair)

Weldmesh Panelled Side Extensions

Ladder Rack

Aluminium Tread Plate Floor Covering

		Maximum Gross Weight	Tyres														
P6e	Single Axle	500kg	145R10	-	•	Option	Option	-	-	-	-	-	-	Option	Option	Option	Option
P6e	Single Axle	750kg	20.5 x 8-10	-	•	Option	Option	-	-	-	-	-	-	Option	Option	Option	Option
P6e	Single Axle	500kg	145R13	-	•	Option	Option	-	-	-	-	-	-	Option	Option	Option	Option
P6e	Single Axle	750kg	145R13	-	•	Option	Option	-	-	-	-	-	-	Option	Option	Option	Option
P7e	Single Axle	750kg	20.5 x 8-10	-	•	Option	Option	-	-	-	-	-	-	Option	Option	Option	Option
P7e	Single Axle	500kg	145R13	-	•	Option	Option	-	-	-	-	-	-	Option	Option	Option	Option
P7e	Single Axle	750kg	145R13	-	•	Option	Option	-	-	-	-	-	-	Option	Option	Option	Option
P6	4' H/R (Single Axle)	1400kg	165R13C	-	•	-	Option	-	-	-	-	-	-	Option	-	-	Std
P6	5' H/R (Single Axle)	1400kg	165R13C	-	•	-	Option	-	-	-	-	-	-	Option	-	-	Std
P8	4' H/R (Single Axle)	1400kg	165R13C	-	•	-	Option	-	-	-	-	-	-	Option	-	-	Std
P8	5' H/R (Single Axle)	1400kg	165R13C	-	•	-	Option	-	-	-	-	-	-	Option	-	-	Std
TA5	8'x4' H/R	2700kg	165R13C	-	•	-	Option	-	-	-	-	-	-	Option	-	-	Option
TA5	10'x4' H/R	2700kg	165R13C	-	•	-	Option	-	-	-	-	-	-	Option	-	-	Option
TA5	12'x4' H/R	2700kg	165R13C	-	•	-	Option	-	-	-	-	-	-	Option	-	-	Option
TA5	8'x6' H/R	2700kg	165R13C	•	•	•	Option	Option	Option	Option	-	-	-	Option	-	-	Option
TA5	10'x6' H/R	2700kg	175/75R16C	•	•	•	Option	Option	Option	Option	-	-	-	Option	-	-	Option
TA5	10'x7' H/R	2700kg	175/75R16C	•	•	•	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
TA5HD	12'x6' H/R	3500kg	175/75R16C	•	•	•	Option	Option	Option	Option	-	-	-	Option	-	-	Option
TA5HD	12'x6' H/R	3500kg	6.50R16C	•	•	•	Option	Option	Option	Option	-	-	-	Option	-	-	Option
TA5HD	12'x7' H/R	3500kg	175/75R16C	•	•	•	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
TA5HD	12'x7' H/R	3500kg	6.50R16C	•	•	•	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
TA510	10'x6' H/R	3500kg	175/75R16C	•	•	•	Option	Option	Option	Option	-	-	-	Option	-	-	Option
TA510	10'x6' H/R	3500kg	6.50R16C	•	•	•	Option	Option	Option	Option	-	-	-	Option	-	-	Option
TA510	10'x7' H/R	3500kg	175/75R16C	•	•	•	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
TA510	10'x7' H/R	3500kg	6.50R16C	•	•	•	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
TA510	12'x6' H/R	3500kg	175/75R16C	•	•	•	Option	Option	Option	Option	-	-	-	Option	-	-	Option
TA510	12'x6' H/R	3500kg	6.50R16C	•	•	•	Option	Option	Option	Option	-	-	-	Option	-	-	Option
TA510	12'x7' H/R	3500kg	175/75R16C	•	•	•	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
TA510	12'x7' H/R	3500kg	6.50R16C	•	•	•	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
TA510	14'x6' H/R	3500kg	6.50R16C	•	•	•	Option	Option	Option	Option	-	-	-	Option	-	-	Option
TA510T	14'x6' H/R (Tri Axle)	3500kg	175/75R16C	•	•	•	Option	Option	Option	Option	-	-	-	Option	-	-	Option
TA510	14'x7' H/R	3500kg	6.50R16C	•	•	•	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
TA510T	14'x7' H/R (Tri Axle)	3500kg	175/75R16C	•	•	•	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option

- Trailer option
 - Not Available
 - Std Standard Fit
- *Single Stock Ramp Door on P6e & P7e models

Trailer fitted with EasyLoad™ Ramp and Aluminium Sheep Deck System

Trailer fitted with Standard Ramp without Sheep Deck

Cross Division

Small Cross Division (for use with Sheep Deck System only)

Wind Deflector

Ramp Gate Extensions (Pair)

Dropside Fittings*

Dropside Kit**

Headboard

6' Long Perforated Galvanized Steel Skids (Pair)

8' Long Perforated Galvanized Steel Skids (Pair)

Integrated Skid Carrier and Prop Stands

Sump Tank

DP Container Removal Kit

Mud Flaps

DP120	10'x6' H/R	3500kg	195/60R12C	•	•	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
DP120	12'x6' H/R	3500kg	195/60R12C	•	•	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
DP120T	12'x6' H/R (Tri Axle)	3500kg	195/60R12C	•	•	Option	Option	Option	Option	Option	Option	-	-	Option	Option	Option	Option
DP120T	14'x6' H/R (Tri Axle)	3500kg	195/60R12C	•	•	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option

H/R - Headroom

*Dropside Fittings must be specified at time of order, factory fit only. **Dropside Kit only available when ordered with dropside fittings.

The Ifor Williams commitment to trailer security

Each trailer is fitted with an ID plate which has a unique serial number etched on it. Additionally, the drawbar (except P6e, P7e, P6 & P8) has a different unique number cut through it, which is virtually impossible to alter without noticeably affecting the appearance of the numbers and galvanized finish.

The transport of animals is subject to The Welfare of Animals (Transport) Order 1997. For further details please contact your local DEFRA (Department for the Environment, Food and Rural Affairs) representative or visit their website: www.defra.gov.uk